


# Code Encryptor II


Patent Pending - Part #CE2R



## Installation Manual Street Smart Security

### Installation

Red	Aux +
Black	Aux -
Yellow	Keypad Data Line (Connect to Caddx KP DATA and GREEN from Gem P400, 600 and 800)
Green	Keypad Data Line (Not used on Caddx and Napco Gem P400, 600, 800)



NOTE: Napco Gem P400-800 connect from yellow of CEII to green of keypad

3

### Mandatory Programming

Programming a User Code is mandatory when using the Code Encryptor II. This gives the Code Encryptor microprocessor a User Code to arm and disarm the panel.

You must use a 4 digit code ONLY. The CEII will not operate properly if you teach it a 3 or 5 digit user code.

- Step 6)** Verify that the four-digit code you plan to teach the Code Encryptor II is a valid four-digit user code. Example: From the keypad, use that four-digit code to arm the panel. If the panel arms, that is a good code. If it does not, program that user code into the alarm panel. – The Code Encryptor II uses that four-digit code to arm and disarm the panel, thus that code must be valid.\*
- Step 7)** Press and **HOLD** the program button on the receiver. The light will come **ON** and stay **ON** for three seconds then turn **OFF**. Once the light turns off, **RELEASE** the program button, the light will begin to flash rapidly.
- Step 8)** Using the keypad, slowly and firmly enter the four-digit user code. (If using a Napco you must press the ON/OFF button to send the four-digit code.)

**IMPORTANT:** If you are using an FBI see page 16 and 17

\*NOTE: We recommend using a user code that the customer cannot change. If the user code that is programmed into the CE Module is changed, the Code Encryptor II will not disarm the alarm panel.

6


### Channel 2 Outputs

(Every time button #2 is pressed, two outputs happen simultaneously.)

Output #1	Momentary Contact Closure for Opening and Closing garage door (See Garage Door Interface)
Output #2	500ma (-) output for 3 minutes, (See Channel 2 Timed Output)

### Garage Door Interface


All garage doors have a wall mounted push button that activates the door via a two-wire connection. Make your connection at the push button switch or at the garage door motor where these two wires terminate. The Code Encryptor II will interface with this connection by attaching the red/white and white wires from the Code Encryptor II to these two wires. If you choose to connect to the motor, trace the wires from the push button to the motor to determine the proper connection point. Most garage doors (except MOM Crusader models) use terminals #1 and #2. For MOM Crusader models, use terminals #2 and #3.



9

### Code Encryptor II

Location of the control module is the most important determining factor for range and reliability of your Code Encryptor. Select a location that is as centrally located as possible. Keep in mind that your customer will want to control the operation of the garage door from the driveway, and will also expect the use of the remote for alarm On/Off in the area of entry and exit.



Since the Code Encryptor uses the communication bus wires from the keypad, you may want to place the receiver in or near the garage to easily control the following

- Easy connection to the garage door push button
- Easy visual LED status mounting location
- Easy connection to the keypad wires for complete alarm control

Although you can wire at the panel, it may reduce labor by installing the Code Encryptor II receiver at the point of entry. In most cases that is the garage which will provide an easy installation for garage door Open/Close, status indicator and alarm controls through the keypad. **DO NOT MOUNT THE CONTROL MODULE IN THE ALARM PANELS METAL ENCLOSURE.**

1

### Wiring and Auto Recognition

#### COMPLETE STEPS 1-8

- Step 1)** Unplug the receiver from the wire harness.
- Step 2)** Wire the Red, Black, Yellow and Green to the keypad. (Some panels may only use 3 wires, refer to page 2, 3 for Caddx and Napco Gem P400, P600, P800.)

RED	Connect to Keypad Red or Aux (+)
BLACK	Connect to Keypad Black or Aux (-)
GREEN	Connect to Keypad Green (Not used on Caddx and Napco Gem P400, P600 and P800)
YELLOW	Connect to Keypad Yellow. For Caddx connect to KP DATA. (For Napco Gem P400, P600 and P800 connect yellow from CEII to green of keypad.)

NOTE: You can make these connections at the panel or at the keypad itself. If you place the Code Encryptor II in the garage or any other location away from the panel you may choose to wire the Code Encryptor II directly to the keypad.

- Step 3)** Make sure the alarm panel is powered up and operating.
- Step 4)** While watching the LED light on the Control module, plug the receiver into the Code Encryptor II harness.
- Step 5)** The LED will blink 1 time on power up, after 2 seconds COUNT the flashes that you see. The corresponding flashes will indicate which panel the Code Encryptor II has detected.

4

### Mandatory Programming Continued

Press and Release button #1	Alarm "Away"
Press and Release button #1	Alarm "Disarm"
Press and Hold for 3 seconds	Alarm "Stay" or "Bypass"

NOTE: The Code Encryptor II will arm in the AWAY mode even if you are outside the house. You do not have to arm the alarm before you exit. We do however recommend that you Arm the alarm system within sight of the status LED or keypad to verify that the alarm has received and responded to your remote request.

SEE PAGE 16 FOR NAPCO AND CADDX .

The Code Encryptor II on the following panels self enroll themselves as a specific keypad address code.

- Napco 1632, 3200, 9600 Address #2
- FBI Addressable Address #8 – SEE PAGE 16 AND 17

DO NOT USE THIS ADDRESS CODE FOR ANY KEYPAD. EXAMPLE: If you are using an Napco 1632, no keypads can use address #2 since the CE II will automatically enroll itself as address #2.

Napco 1632, 3200 and 9600 panels must programmed for a second keypad. If you choose to use PANIC, you must also program that feature "ON" for keypad #2. The second keypad must be programmed to area #1 for the CEII to operate.

- 1632 Address 0724 (\*1) and Address 0731 (\*4)
- 3200 Address 2426 (\*1) and Address 2441 (\*4)
- 9600 Address 2426 (\*1) and Address 2441 (\*4)


7

### Channel 2 Timed Output

Every time you press button 2 on the Code Encryptor II remote the Gray wire sends a 500ma (-) output for 3 minutes.

**Application #1** - If you hardwire the garage door you can use this output to trigger a 12VDC relay that will energize when you open or close your garage door extending your entry/exit delay by another 3 minutes. For security, you can make the entry delay minimal so if a thief enters through the garage, the entry delay will be short. If the homeowner opens the garage with our Code Encryptor II we will extend the entry delay by 3 minutes. If you are using the status output in the garage then you may not need this extra time, as our remote can immediately de-activate the alarm system and you will receive visual indication the alarm is disarmed. NOTE: If you are using this output see additional programmability on page 20.

**Application #2** - You can use this output to drive entry/exit illumination. Every time the customer enters or exits the house this output can trigger a relay or an X-10 powerflash module to interface with driveway, porch or Malibu lighting, illuminating their way as they leave and return home. The output activates automatically when you press button 2 on the Code Encryptor II remote and will shut off after 3 minutes. NOTE: If you are using this output see additional programmability on page 20.



10

### Wiring Diagram

Green	Connect to green of keypad (Not used on Caddx or Napco Gem P400, P600, P800, Express 400, 600)
Yellow	Connect to yellow of keypad (Caddx connect to KP DATA) <b>IMPORTANT:</b> For Napco Gem P400, P600, P800 and Express 400, 600 connect the yellow from the CEII to the green of the keypad.
Gray	(-) Channel 2 Timed Output
Red/White	Channel 2 N/O relay (Garage Door Pushbutton)
White	Channel 2 Common (Garage Door Pushbutton)
Brown	Channel 3 Common (5amp)
Brown/White	Channel 3 N/O (5amp)
Blue/Green	Channel 3 N/C (5amp)
Red	+12VDC
Black	(-) Ground
Purple	LED (-) Output

Napco Gem P400-800  
SEE SPECIAL WIRING



Button 1	Alarm ON/OFF/STAY**
Button 2	Garage Door OPEN/CLOSE
Button 3	PANIC OUTPUT Hold for 3 seconds RELAY OUTPUT Press and Release

\*\*Press and hold for 3 seconds to activate "STAY" or "BYPASS" mode 2

### Automatic Recognition Continued:


Number of Flashes	Alarm Panel detected by the CE II
1	No Alarm connected (CE II defaults to relay mode) SEE PAGE 15 "Default Mode"
2	FBI using a 4600 style keypad
3	FBI using a 4612 style keypad
4	FBI using an addressable keypad SEE PAGE 16 and 17
5	Napco 1632, 3200, 9600
6	Caddx NX4, NX6, NX8
7	Napco Gem P400, P600, P800, Express 400, 600

Go to Mandatory Programming (Steps 6, 7 and 8)

NOTE: If the CEII does not detect correctly, call Technical Toll Free 888-768-2846 7am-5pm PST

### LED Wiring

DO NOT CONNECT LED DIRECTLY TO GROUND!



The LED is a low voltage type and must run through the Code Encryptor II. If you attempt to connect the purple wire directly to ground (-) the LED will burn and will NOT operate again.

Go TO Channel 2 Outputs

8

### Channel 3 Applications

Press and Release button #3	See Relay Output
Press and Hold button #3 for seconds	See Panic Mode

### Relay Output

(Not applicable for Napco/Caddx panels if you are using the feature on page 16.)

Occasionally, you may want to use Channel 3 for control of optional accessories (i.e., Malibu lighting, sprinklers, X-10 automation). The Code Encryptor II provides the ability to reconfigure Channel 3 to a variety of popular outputs using the on-board jumpers. The output provided from the Code Encryptor II is a 5amp from C relay (Common, N/O, N/C).

#### Jumper Configuration

- Both jumpers in (default)
- Jumper closest to the harness removed
- Jumper farthest from the harness removed
- Both jumpers out

#### Channel 3 Output Type

- Momentary output
- Latching (on/off) output
- 75sec timed output
- 150sec timed output (not applicable if using the feature on page 16)

This output is a 5amp Form C relay (Common, N/O/, N/C). To energize relay, press and release button number 3 (the smallest button). You must RELEASE the button before the relay will energize.

11

## Panic Mode

Press and hold button 3 on the remote control for at least 3 seconds. This will cause the panel to go into a panic mode. Press button 1 (largest button) to disarm the panel.

Napco 1632, 3200 and 9600 panels must be programmed for keypad #2 panic "ON". SEE PAGE 7 for the Napco Program Guide.

If you are using a panel that does not have a default setting for keypad panic you must program that option "ON" before our system will operate. Most manufacturers set the keypad Panic as a default setting.

### DEACTIVATING THE PANIC FEATURE:

In the event the user does not want to access a panic button through the remote control, it can be de-activated from the Code Encryptor II's memory.

- Step 1) Unplug the wire harness from the Code Encryptor II.
- Step 2) Press and HOLD the program button.
- Step 3) While HOLDING the program button, plug the Code Encryptor II harness back in. The LED light located on the front will turn ON.
- Step 4) Wait until the light turns "OFF".
- Step 5) Once the light has turned "OFF" release the button


12

### DEFAULT MODE:

- If the Code Encryptor II fails to recognize any of the data coming from the keypad wires, it will automatically default to a relay mode for button #1
- If this happens, verify that you are properly wired to one of the alarms listed on page 5.
- If you have connected the CE II to an alarm it does not recognize, follow the wiring below for a keyswitch mode.
- Program a selected zone as "Keyswitch Arming."
- Do not use the green or yellow wires.

## Installation for Keyswitch Arming

- Red Aux +
- Black Aux -
- Brown/White Zone programmed for keyswitch arming
- Brown Common adjacent to zone



15

## Troubleshooting

**PROBLEM:** I press Button #1 (largest, button) but nothing happens.  
**SOLUTION:** 1) Did you teach the Code Encryptor II a VALID four-digit user code?  
*Note: The code you teach the Code Encryptor II must be a master code or one of the current user codes.*

2) Press button #2 (middle button), if you do NOT hear a "click" at the receiver, GO TO PAGE 14 and learn that remote into the Code Encryptor II.

**PROBLEM:** I press and hold button #3 (smallest button) and I do not get a panic.  
**SOLUTION:** 1) Did you program the panel for keypad panic?

2) To program the Code Encryptor II for panic GO TO PAGE 13.

**PROBLEM:** Unit does not seem to identify the panel I am using.  
**SOLUTION:** Call technical 888-768-2846.

**PROBLEM:** I am using an FBI panel but the system won't operate.  
**SOLUTION:** 1) Verify that NO KEYPADS are set to address #8.  
 2) Enter and exit programming to have the panel poll for keypads or a CEII unit. (SEE PAGE 16 and 17)

**PROBLEM:** I am using a Napco 1632, 3200 or 9600 and the remote will not arm or disarm.

**SOLUTION:** 1) Verify the NO KEYPADS are set to address #2  
 2) Did you program Keypad #2 to Area #1 (SEE PAGE 7)

18

## Panic Continued

### ACTIVATING THE PANIC MODE

**NOTE: This is the default setting of the Code Encryptor II.**


If you have previously programmed remote panic "OFF" and would like to turn it back "ON" follow the steps below. If this is a NEW installation Panic "ON" is the DEFAULT setting for the Code Encryptor II.

- Step 1) Unplug the wire harness from the Code Encryptor II.
- Step 2) Press and HOLD the program button.
- Step 3) While HOLDING the program button, plug the Code Encryptor II harness back in. The LED light located on the front will turn ON.
- Step 4) Immediately release the program button.

### IF NECESSARY, PROGRAM THE ALARM PANEL FOR KEYPAD PANIC.

## Napco/Caddx Panels

- If a zone is programmed for "HOME/AWAY BYPASS" or AUTO-BYPASS", the alarm will bypass that zone unless as "ENTRY/EXIT" zone is tripped after arming.
  - If you wish to have a zone programmed as mentioned above, the CEII can be installed to allow you to arm the panel in the "AWAY" mode from outside the house.
- Step 1) Remove BOTH jumpers from the CEII control module. They are located next to the wire harness
  - Step 2) Connect the Channel 3 wires to the zone programmed for "ENTRY/EXIT". When armed with the CEII remote, the relay will energize for 1 second, causing the zone to be tripped and arm the alarm in the "AWAY" mode.



## FBI Addressable Keypads

- When using an addressable keypad like an XK-7LC, XK-5LC, XK-508, XK-512, XK-516, XK-708, XK-716 you may have to complete an extra step before the CEII will operate. SEE PAGE 17.

13

## To Add or Delete Remotes

### TO ADD A NEW REMOTE

#### METHOD #1

To add a remote to your Code Encryptor II, disarm the panel and Enter 78738, (if using a Napco 1632, 3200 or 9600 press the ON/OFF to send the data.) from the keypad. The system will arm in the "STAY" mode. Press and release button #1 (largest button on the remote control) until the arm system disarms. It should take a total of four presses.

#### METHOD #2

To add a remote to your Code Encryptor II PRESS AND RELEASE the program button on the receiver. The light on the receiver will come ON. Immediately PRESS button 1 (largest button) on the new remote control THREE TIMES. The light on the receiver should go OFF, indicating the remote has been learned. If the light on the receiver stays ON, the remote has not been learned. Remove and replace the harness, wait 15 seconds while auto recognition occurs and follow these instructions again.

The Code Encryptor II can hold up to seven remotes.

14

## FBI Addressable Continued

- These FBI panels poll for addressable or non addressable keypads upon power up OR after you exit programming. Since the CEII requires that you plug it in after the FBI is powered up, it misses that polling loop.

TO have the FBI panel Re-Poll for keypads and CEII units

Step 1) Enter Programming Mode: Press "CODE" + "\*" and installers code (2468 default) followed by a "1".

Step 2) Exit Programming by pressing the "STAY" key.

Step 3) The CEII will enroll itself as an Addressable Keypad at address #8

## To Delete ALL Remotes

### METHOD #1

To delete a lost or stolen remote from the Code Encryptor II, you must purge the entire memory. This will delete all of the current remotes. You will then have to add them back in one at a time. To purge the memory, disarm the panel. Enter 76278, (if using a Napco 1632, 3200 or 9600 press the ON/OFF to send the data), from the keypad. The keypad on most panels will "beep" or the lights will turn off momentarily to confirm delete. Follow the instructions on page 14 (To Add a New Remote).

### METHOD #2

To delete a lost or stolen remote from the Code Encryptor II, you must purge the entire memory. This will delete all of the current remotes. You will then have to add them back into memory. To purge, PRESS AND HOLD the program button, the light will come ON for four seconds, then go OFF, and finally it will come ON again, indicating that all the remotes in memory have been purged. Release the program button and follow the instructions on page 14 (To Add a New Remote).

17

## Specifications

### RECEIVER

- 12VDC Power Input
- Channels 1 Data outputs
- Channel 2 Relay N/O, Comm (10amp)
- Channel 3 selectable: Form C Relay (N/O, N/C, Comm) 5amp  
 This output can be reconfigured from a pulsed output to a latching, 75 second timed or 150 second timed output.
- Channel 3 - Keypad panic data output (Programmable On or OFF)

Frequency 303Mhz

Stand by Power Consumption 15ma

Temperature Range -5°F to 160°F (Indoor use only)

### REMOTE CONTROL

Battery 12VDC Mini (Part #GP23A) Replace battery at least once a year.

Range 150+ feet

### CHANNEL 3 OUTPUT

Both jumpers in (default)	Momentary output
Jumper closest to the harness removed	Latching (on/off) output
Jumper farthest from the harness removed	75sec timed output
Both jumpers out	150sec timed output (not applicable if using the feature on page 16)

STREET SMART SECURITY TECHNICAL CAN BE REACHED AT:  
 12925 Brook Printer Place, Suite 410, Poway, CA 92064  
 M-F 7AM-5PM PST AT (888) 768-2846 OR (619) 513-9352-FAX 19

## Federal Communications Commission (FCC) Statement

This equipment has been tested to FCC requirements and has been found acceptable for use. The FCC requires the following statement for your information:

This equipment generates and uses radio frequency energy and if not installed and used properly, that is, in strict accordance with the manufacturer's instructions, may cause interference to radio and television reception. It has been type tested and found to comply with the limits for a Class B computing device in accordance with the specifications in Part 15 of FCC Rules, which are designed to provide reasonable protection against such interference in a residential installation. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause interferences to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- If using an indoor antenna, have a quality outdoor antenna installed.
- Reorient the receiving antenna until interference is reduced or eliminated
- Move the receiver away from the control/communicator.
- Move the antenna leads away from any wire runs to the control/communicator.
- Plug the control/communicator into a different outlet so that it and the receiver are on different branch circuits.

If necessary, the user should consult the dealer or an experienced radio/television technician for additional suggestions.

The user or installer may find the following booklets prepared by the Federal Communications Commission helpful: "Interference Handbook"  
 This booklet is available from the U.S. Government Printing Office, Washington, DC 20402. The user shall not make any changes or modifications to the equipment unless authorized by the installation instructions or User's Manual. Unauthorized changes or modifications could void the user's authority to operate the equipment.

21

## Optional Reversible Outputs

Channel 2 has two independent outputs that occur when button #2 is pressed. The first output is a momentary relay contact closure which is intended for the use of opening and closing a garage door. This is the primary output and can not be changed or reconfigured. The second output is a (-) 500ma transistor output to provide a zone bypass or illuminated entry/exit.

- If you are not using the relay for Channel 3 you may choose to swap the (-) transistor output for the relay. In this instance you will then have two contact closures every time Button # 2 is pressed. The standard momentary contact closure and ALSO a Form C relay that will energize automatically for 3 minutes every time the garage door is opened or closed.

To Swap the transistor and relay outputs.

Step 1) While watching the LED on the CE II receiver press and HOLD button 1 and 3 simultaneously on the remote control until the LED on the CE II receiver illuminates. (approx. 5 seconds)

Step 2) To make channel 2 a relay press the program button on the CE II Receiver TWICE, to make it a transistor output press ONCE (Default setting)

Step 3) Wait 10 seconds and the CE II will automatically reconfigure the outputs.

NOTE- Even if you swap outputs, the Panic button will still operate if you press and HOLD button #3 for three seconds.

**IMPORTANT**  
 This feature will not work for NAPCO/CADDX if you are using the feature on page 16.

20

## Canadian Department of Communications (DOC) Statement

**NOTICE:** The Canadian Department of Communications label identifies certified equipment. This certification means that the equipment meets certain telecommunications network protective, operational and safety requirements. The Department does not guarantee the equipment will operate to the user's satisfaction. Before installing this equipment, users should ensure that it is permissible to be connected to the facilities of the local telecommunications company. The equipment must also be installed using an acceptable method of connection. In some cases, the company's inside wiring associated with a single line individual service may be extended by means of certified connector assembly (telephone extension cord). The customer should be aware that compliance with the above conditions may not prevent degradation of service in some situations.

Repairs to certified equipment should be made by an authorized Canadian maintenance facility designed by the supplier. Any repairs or alterations made by the user to this equipment, or equipment malfunctions, may give the telecommunications company cause to request the user to disconnect the equipment.

Users should ensure for their own protection that the electrical ground connections of the power utility, telephone lines and internal metallic water pipe system, if present, are connected together. This precaution may be particularly important to rural areas.

**CAUTION:** User should not attempt to make such connections themselves, but should contact the appropriate electric inspection authority, or electrician, as appropriate.

The Load Number (LN) assigned to each terminal device denotes the percentage of the total load to be connected to a telephone loop which is used by the device, to prevent overloading. The termination on a loop may consist of any combination of devices subject only to the requirement that the total of the Load Numbers of all the devices does not exceed 100.

23

22